## §761.304

portions so that they are clearly identified. Determine the sample location in each portion as directed in §761.304.

- (1) For large nearly flat surfaces contaminated by a single source of PCBs with a uniform concentration, assign each 1 meter square surface a unique sequential number.
- (i) For three or fewer 1 meter square areas, sample all of the areas.
- (ii) For four or more 1 meter square areas, use a random number generator or table to select a minimum of 10 percent of the areas from the list, or to select three areas, whichever is more.
- (2) For other large nearly flat surfaces, sample all of the one meter square areas.
- (b) Small or irregularly shaped surfaces. For small surfaces having irregular contours, such as hand tools, natural gas pipeline valves, and most exterior surfaces of machine tools, sample the entire surface. Any person may select sampling locations for small, nearly flat surfaces in accordance with §761.308 with the exception that the maximum area in §761.308(a) is <1 meter square.
- (c) *Preparation of surfaces*. Drain all free-flowing liquids from surfaces and brush off dust or loose grit.

## § 761.304 Determining sample location.

- (a) For 1 square meter non-porous surface areas having the same size and shape, it is permissible to sample the same 10 cm by 10 cm location or position in each identical 1 square meter area. This location or position is determined in accordance with §761.306 or §761.308.
- (b) If some 1 square meter surfaces for a larger non-porous surface area have different sizes and shapes, separately select the 10 cm by 10 cm sampling position for each different 1 square meter surface in accordance with §761.308.
- (c) If non-porous surfaces have been cleaned and the cleaned surfaces do not meet the applicable standards or levels, surfaces may be recleaned and resampled. When resampling surfaces previously sampled to verify cleanup levels, use the sampling procedures in §§ 761.306 through 761.316 to resample the surfaces. If any sample site selected coincides with a previous sam-

pling site, restart the sample selection process until all resampling sites are different from any previous sampling sites.

## § 761.306 Sampling 1 meter square surfaces by random selection of halves.

- (a) Divide each 1 meter square portion where it is necessary to collect a surface wipe test sample into two equal (or as nearly equal as possible) halves. For example, divide the area into top and bottom halves or left and right halves. Choose the top/bottom or left/right division that produces halves having as close to the shape of a circle as possible. For example, a square is closer to the shape of a circle than is a rectangle and a rectangle having a length to width ratio of 2:1 is closer to the shape of a circle than a rectangle having a length to width ratio of 3:1.
- (b) Assign a unique identifier to each half and then select one of the halves for further sampling with a random number generator or other device (i.e., by flipping a coin).
- (c) Continue selecting progressively smaller halves by dividing the previously selected half, in accordance with paragraphs (a) and (b) of this section, until the final selected half is larger than or equal to 100 cm<sup>2</sup> and smaller than 200 cm<sup>2</sup>.
- (d) Perform a standard PCB wipe test on the final selected halves from each 1 meter square portion.
- (e) The following is an example of applying sampling by halves. Assume that the area to sample is a 1 meter square surface area (a square that has sides 1 meter long). Assign each half to one face of a coin. After flipping the coin, the half assigned to the face of the coin that is showing is the half selected.
- (1) Selecting the first half:
- (i) For a square shape the top/bottom halves have the same shape as the left/right halves when compared to a circle, i.e., regardless of which way the surface is divided, each half is 1 half meter wide by 1 meter long. Therefore, divide the area either top/bottom or left/right. For selecting the first half, this example will select from left/right halves.
- (ii) A coin flip selects the left half. The dimensions of this selected surface